

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

MANUFACTURER'S NAME: ADDRESS:
DISTINCTIVE IMAGE 50 COMMERCE PARKWAY
HODGENVILLE, KY 42748

EMERGENCY PHONE : (800) 424 - 9300
INFORMATION PHONE : (800) 223 - 1918
FAX NUMBER : (800) 500 - 9812

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, clear

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE EYE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Unlikely to cause skin irritation or injury.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing of vapor or mist is possible. It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions), blood-forming system

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, coma

Target Organs

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / trade secret no.	Concentration
Acetone	67-64-1	90 - 100%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures

until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information

Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapors/mists with a water spray jet.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Acetone

67-64-1

ACGIH	8-hour, time-weighted average	500 ppm
ACGIH	Short-term exposure limit	750 ppm
NIOSH	Time-weighted average	250 ppm concentration for up to a 10-hour work day during a 40-hour work week
NIOSH	Time-weighted average	590 mg/m ³ concentration for up to a 10-

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

		hour work day during a 40-hour work week
OSHA	Short-term exposure limit	2,400 mg/m ³
OSHA	8-hour time weighted average	1,000 ppm
OSHA	8-hour time weighted average	2,400 mg/m ³
OSHA	8-hour time weighted average	750 ppm
OSHA	8-hour time weighted average	1,800 mg/m ³
OSHA	Short-term exposure limit	1,000 ppm

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Color	clear
Odor characteristic	
Boiling point/boiling range	133 °F / 56 °C
pH	7
Flash point	0 °F / -18 °C
Lower explosion limit/Upper explosion limit	2.1 %(V) / 13 %(V)
Vapor pressure	18.530 mmHg @ 68 °F / 20 °C
Density	0.790 g/cm ³ @ 68 °F / 20 °C 6.59 lb/gal @ 68 °F / 20 °C
Water solubility	soluble
Partition coefficient: n-octanol/water	0.2
Viscosity, dynamic	0.3 mPa-s

10. STABILITY AND REACTIVITY**Stability**

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

Stable.

Conditions to avoid

Heat, flames and sparks.

Incompatible products

Acids, alkalis, Amines, Ammonia, halogens, peroxides, Reducing agents, Strong oxidizing agents

Hazardous decomposition products carbon dioxide and carbon monoxide

Hazardous reactions

Product will not undergo hazardous polymerization.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute oral toxicity - : no data available

Product

Acute oral toxicity – Components

Acetone : LD50: 5,800 mg/kg Species: rat Symptoms: tremors

Acute inhalation toxicity

Acute inhalation toxicity - : no data available Product

Acute inhalation toxicity – Components

Acetone : LC50: 16,000 mg/l Exposure time: 4 h Species: rat

Acute dermal toxicity

Acute dermal toxicity - : no data available

Product

Acute dermal toxicity – Components

Acetone : LD50: 7,426 mg/kg Species: guinea pig

Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability – Product : no data available

Biodegradability – Components

Acetone : Remarks: Readily biodegradable

Bioaccumulation

Bioaccumulation – Product : no data available

Ecotoxicity effects

Toxicity to fish

Toxicity to fish – Product : no data available

Toxicity to fish – Components

Acetone : LC50: 6,100 mg/l

Exposure time : 48 h

Species: Oncorhynchus mykiss

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

(rainbow trout)

Toxicity to daphnia and other aquatic invertebrates

Toxicity to daphnia and other aquatic invertebrates -
Product

: no data available

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

Toxicity to daphnia and other aquatic invertebrates – Components

Acetone : EC50: 7,630 mg/l
 Exposure time: 48 h
 Species: Daphnia magna (Water flea)
 Test substance: Acetone

Toxicity to algae

Toxicity to algae - Product : no data available

Toxicity to algae – Components

Toxicity to bacteria

Toxicity to bacteria - Product : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

Acetone
 Remarks: no data available

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
U.S. DOT - ROAD					
UN 1090	Acetone	3		II	
U.S. DOT - RAIL					
UN 1090	ACETONE	3		II	
U.S. DOT - INLAND WATERWAYS					
UN 1090	ACETONE	3		II	
TRANSPORT CANADA - ROAD					
UN 1090	ACETONE	3		II	
TRANSPORT CANADA - RAIL					
UN 1090	ACETONE	3		II	
TRANSPORT CANADA - INLAND WATERWAYS					
UN 1090	ACETONE	3		II	
INTERNATIONAL MARITIME DANGEROUS GOODS					
UN 1090	ACETONE	3		II	
INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO					
UN 1090	Acetone	3		II	
INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER					
UN 1090	ACETONE	3		II	
MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES					
UN 1090	ACETONA	3		II	

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Benzene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Benzene

WARNING! This product contains a chemical known to the State of California to cause cancer.

Benzene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Benzene

SARA Hazard Classification

SARA 311/312

Classification

Fire Hazard

Acute Health Hazard

New Jersey RTK Label Information

Acetone 67-64-1

Pennsylvania RTK Label Information

Acetone 67-64-1

Notification status

US. Toxic Substances Control Act y (positive listing)

Canada. Canadian Environmental Protection Act (CEPA).

Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) y (positive listing)

Australia. Industrial Chemical (Notification and Assessment) Act y (positive listing)

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand y (positive listing)

Japan. Kashin-Hou Law List y (positive listing)

Korea. Toxic Chemical Control Law (TCCL) List y (positive listing)

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act y (positive listing)

China. Inventory of Existing Chemical Substances y (positive listing)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302) 5000 lbs

Reportable quantity-Components

Acetone 67-64-1 5000 lbs

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

	HMIS	NFPA
Health	2	2
Flammability	3	3
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

SAFETY DATA SHEET

Revision Date: 07/18/2013

Print Date: 11/25/2014

MSDS Number: 100000001956

DI-ACETONE ACETONE

52705

Version: 1.2

VOC and HAP Regulatory Sheet ver. 1.0

VOC Percent	0.00%
VOC Content, less water and exempt solvents	0.00%
VOC Vapor Pressure	0.00 mm of Hg
Calculated HAP Total	0.00%
Calculated HAP total	0.00%
Method	Calculated from the formulation consistent with the U.S. EPA VOC definition [40 CFR 51.100(s)]

This information has been gratuitously provided by Cumberland Products Incorporated. Although it is intended to be accurate, CUMBERLAND PRODUCTS INCORPORATED DISCLAIMS ANY AND ALL LIABILITY, EITHER EXPRESS OR IMPLIED. Any information claimed by Cumberland Products Inc. to be confidential or proprietary is not to be disclosed to any third party.