

# Material Safety Data Sheet

Hexane

Page 1 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 DI-HEXANE

## Section 1 - Chemical Product and Company Identification

**MSDS Name:** Hexane

**Product Grade :** SQ, ExcelsR, HPLC

**Catalog Numbers:** 34205, 34206, 34207, 12815, 43586

**Synonyms:** Hexane, Hexane 65°C-70°C(95%) Fraction from Petroleum

**Company Identification:**

**MANUFACTURER'S NAME:**

DISTINCTIVE IMAGE

**ADDRESS:**

50 COMMERCE PARKWAY  
HODGENVILLE, KY 42748

EMERGENCY PHONE : (800) 424 - 9300

INFORMATION PHONE : (800) 223 - 1918

FAX NUMBER : (800) 500 - 9812

## Section 2 - Composition, Information on Ingredients

CAS#	Chemical Name	Percent	EINECS/ ELINCS
110-54-3			

## Section 3 - Hazards Identification

### EMERGENCY OVERVIEW

#### Potential Health Effects

**Eye:** Causes mild eye irritation.

**Skin:** Prolonged and/or repeated contact may cause defatting of the skin and dermatitis. Causes irritation with burning pain, itching, and redness. Absorbed through the skin. There have been no reports of skin sensitization in people occupationally exposed to n-hexane. Skin sensitization was not observed in a maximization test using 25 volunteers.

**Ingestion:** May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. May cause central nervous system depression.

**Inhalation:** Causes respiratory tract irritation. Exposure produces central nervous system depression. Vapors may cause dizziness or suffocation. n-Hexane vapor concentrations can become so high that oxygen is displaced, especially in confined spaces.

**Chronic:** Prolonged or repeated skin contact may cause defatting and dermatitis. Prolonged or repeated exposure may cause adverse reproductive effects. Chronic exposure may cause visual disturbances. Laboratory experiments have resulted in mutagenic effects. Peripheral neuropathy symptoms include: muscular weakness, paresthesia, numbing of the hands, feet, legs and arms, unsteadiness, and difficulty in walking and standing. Repeated exposure may cause nervous system abnormalities with muscle weakness and damage, motor incoordination, and sensation disturbances. Chronic exposure produces peripheral neuropathy.

# Material Safety Data Sheet

Hexane

Page 2 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 DI-HEXANE

## Section 4 - First Aid Measures

**Eyes:** In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes. Get medical aid.

**Skin:** In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

**Ingestion:** Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

**Notes to Physician:** Treat symptomatically and supportively. For ingestion, the stomach should be intubated, aspirated, and lavaged with a slurry of activated charcoal-protect the airway from aspiration of gastric contents. Monitor arterial blood gases in cases of severe aspiration.

## Section 5 – Fire Fighting Measures

**General Information:** As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/N IOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Use water spray to keep fire-exposed containers cool. May accumulate static electrical charges, and may cause ignition of its own vapors. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. This liquid floats on water and may travel to a source of ignition and spread fire.

**Extinguishing Media:** Use dry chemical, carbon dioxide, or appropriate foam. Solid streams of water may be ineffective and spread material. Water may be ineffective because it will not cool material below its flash point.

**Flash Point:** -22° to -26.1° F

**Autoignition Temperature:** 225° C ( 437.000° F)

**Explosion Limits. Lower:**1.2 vol %

**Upper:** 7.7 vol %

**NFPA Rating:** (estimated) Health: 2; Flammability: 3; Instability: 0

## Section 6 – Accidental Release Measures

**General Information:** Use proper personal protective equipment as indicated in Section 8.

**Spills/Leaks:** Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Provide ventilation. A vapor suppressing foam may be used to reduce vapors. Use only non-sparking tools and equipment.

## Section 7 - Handling and Storage

**Handling:** Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be

# Material Safety Data Sheet

## Hexane

Page 3 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 DI-HEXANE

dangerous. Take precautionary measures against static discharges. Keep away from heat, sparks and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor or mist.

**Storage:** Keep away from heat and flame. Keep away from sources of ignition. Store in a tightly closed container. Keep from contact with oxidizing materials. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area.

### Section 8 - Exposure Controls, Personal Protection

**Engineering Controls:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local explosion-proof ventilation to keep airborne levels to acceptable levels.

#### Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final P ELs
Hexane (contains a mixture of isomers)	50 ppm TWA; Skin - potential significant contribution to overall exposure by the cutaneous route	50 ppm TWA; 180 mg/m <sup>3</sup> TWA 1100 ppm IDLH	500 ppm TWA; 1800 mg/m <sup>3</sup> TWA

**OSHA Vacated PELs:** Hexane (contains a mixture of isomers): 50 ppm TWA; 180 mg/m<sup>3</sup> TWA

#### Personal Protective Equipment

**Eyes:** Wear chemical splash goggles.

**Skin:** Wear appropriate protective gloves to prevent skin exposure.

**Clothing:** Wear appropriate protective clothing to prevent skin exposure.

**Respirators:** A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

### Section 9 - Physical and Chemical Properties

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	clear colorless
<b>Odor:</b>	gasoline-like
<b>pH:</b>	Not available.
<b>Vapor Pressure:</b>	151 mm Hg @ 25 deg C
<b>Vapor Density:</b>	2.97(Air = 1)
<b>Evaporation Rate:</b>	Not available.
<b>Viscosity:</b>	0.31 mPas 20 deg C
<b>Boiling Point:</b>	62 - 69 deg C @ 760 mmHg
<b>Freezing/Melting Point:</b>	-95 deg C
<b>Decomposition Temperature:</b>	Not available.
<b>Solubility:</b>	Insoluble.
<b>Specific Gravity/Density:</b>	0.678
<b>Molecular Weight:</b>	86.18
<b>Molecular Formula:</b>	C <sub>6</sub> H <sub>14</sub>

# Material Safety Data Sheet

Hexane

Page 4 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 DI-HEXANE

## Section 10 - Stability and Reactivity

**Chemical Stability:** Stable under normal temperatures and pressures.

**Conditions to Avoid:** Ignition sources, excess heat, electrical sparks, confined spaces.

**Incompatibilities with Other Materials:** Strong oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide.

**Hazardous Polymerization:** Will not occur.

## 11. – Toxicological Information

**RTECS#:**

**CAS#** 110-54-3: MN9275000

**LDSO/LCSO:**

CAS# 110-54-3:

Draize test, rabbit, eye: 10 mg Mild;

Inhalation, mouse: LC50 = 150000 mg/m<sup>3</sup>/2H; Inhalation,

rat: LC50 = 48000 ppm/4H;

Inhalation, rat: LC50 = 627000 mg/m<sup>3</sup>/3M;

Oral rat: LD50 = 25 gm/kg;

**Carcinogenicity:**

CAS# 110-54-3: Not listed by ACG IH, IARC, NTP, or CA Prop 65.

**Epidemiology:** Occupational polyneuropathy has resulted from hexane exposures as low as 500 ppm, but the minimum levels of n-hexane that are neurotoxic in humans haven't been established. Nearly continuous exposure of animals at 250 ppm has caused neurotoxic effects.

**Teratogenicity:** No evidence of teratogenicity or embryo toxicity in animal studies with hexane. Fetotoxicity has been observed in the presence of maternal toxicity.

**Reproductive Effects:** Severe testicular damage has been observed in rats exposed to hexane at concentrations which have produced other significant toxicity. Although sub neurotoxic doses of its principle toxic metabolite, 2,5-hexanedione, can induce progressive testicular toxicity in rats, there have been no reports of human sterility or other reproductive toxicity associated with n-hexane exposures.

**Mutagenicity:** Positive results (chromosomal damage in the bone marrow cells) obtained for rats exposed by inhalation to n-hexane.

**Neurotoxicity:** n-Hexane is a mild irritant and CNS depressant in acute exposure, but its principal effects are damage to the sensory and motor peripheral nerves, particularly in chronic exposure.

**Other Studies:**

## Section 12 - Ecological Information

**Ecotoxicity:** No data available. Estimated BCF values = 2.24 and 2.89. These values suggest that hexane will show low bioconcentration in aquatic organisms. Estimated Koc value = 4.11. This product will show slight soil mobility and is expected to rapidly volatilize from moist surface soils.

**Environmental:** Terrestrial: Volatilization and adsorption are expected to be the most important fate processes. Aquatic: Photolysis or hydrolysis are not expected to be important. Atmospheric: Expected to exist entirely in the vapor phase in ambient air, expected half life 2.8 days. Expected to biodegrade but not bioconcentrate.

**Physical:** No information available.

**Other:** No information available.

# Material Safety Data Sheet

Hexane

Page 5 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 DI-HEXANE

## Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**RCRA P-Series:** None listed.

**RCRA U-Series:** None listed.

## Section 14 - Transport Information

	US DOT	Canada TDG
<b>Shipping Name:</b>	HEXANES	HEXANES
<b>Hazard Class:</b>	3	3
<b>UN Number:</b>	UN1208	UN1208
<b>Packing Group:</b>	II	II
<b>Additional Info:</b>		FLASHPO INT -22C

## Section 15 - Regulatory Information

### US FEDERAL

#### TSCA

CAS# 110-54-3 is listed on the TSCA inventory.

#### Health & Safety Reporting List

None of the chemicals are on the Health & Safety Reporting List.

#### Chemical Test Rules

None of the chemicals in this product are under a Chemical Test Rule.

#### Section 12b

None of the chemicals are listed under TSCA Section 12b.

#### TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

#### CERCLA Hazardous Substances and corresponding RQs

CAS# 110-54-3: 5000 lb final RQ; 2270 kg final RQ

#### SARA Section 302 E, Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

#### SARA Codes

CAS # 110-54-3: immediate, delayed, fire.

#### Section 313

This material contains Hexane (contains a mixture of (CAS# 110-54-3, 100%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR

#### Clean Air Act:

CAS# 110-54-3 is listed as a hazardous air pollutant (HAP).

This material does not contain any Class 1 Ozone depletors.

This material does not contain any Class 2 Ozone depletors.

#### Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the

# Material Safety Data Sheet

Hexane

Page 6 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 DI-HEXANE

## **CWA.**

**None of the chemicals in this product are listed as Priority Pollutants under the CWA.**

**None of the chemicals in this product are listed as Toxic Pollutants under the CWA.**

## **OSHA:**

**None of the chemicals in this product are considered highly hazardous by OSHA.**

## **STATE**

**CAS# 110-54-3 can be found on the following state right to know lists: New Jersey, Pennsylvania, Minnesota, Massachusetts.**

## **California Prop 65**

**California No Significant Risk Level: None of the chemicals in this product are listed.**

## **European/International Regulations**

### **European Labeling in Accordance with EC Directives Hazard Symbols:**

XN F N

### **Risk Phrases:**

R 11 Highly flammable.

R 38 Irritating to skin.

R 48/20 Harmful : danger of serious damage to health by prolonged exposure through inhalation.

R 62 Possible risk of impaired fertility.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapors may cause drowsiness and dizziness.

### **Safety Phrases:**

S 16 Keep away from sources of ignition - No smoking.

S 29 Do not empty into drains.

S 33 Take precautionary measures against static discharges.

S 36/37 Wear suitable protective clothing and gloves.

S 9 Keep container in a well-ventilated place.

S 61 Avoid release to the environment. Refer to special instructions /safety data sheets.

S 62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

### **WGK (Water Danger/Protection)**

CAS# 110-54-3: 1

### **Canada - DSL/NDSL**

CAS# 110-54-3 is listed on Canada's DSL List.

### **Canada - WHMIS**

This product has a WHM IS classification of B2, D2B.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

### **Canadian Ingredient Disclosure List**

CAS# 110-54-3 is listed on the Canadian Ingredient Disclosure List.

## **Section 16 – Other Information**

**Disclaimer:** The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume

# Material Safety Data Sheet

Hexane

Page 7 of 7

Revision Date: 07/01/2013

Print Date: 12/3/2014

ACC# 10951 **DI-HEXANE**

no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fisher be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fisher has been advised of the possibility of such damages.